



US006278688B1

(12) **United States Patent**
Suutari et al.

(10) **Patent No.:** US 6,278,688 B1
(45) **Date of Patent:** Aug. 21, 2001

(54) **PROCEDURE FOR ENSURING THE OPERATION OF SIGNALLING CHANNELS IN A V5 INTERFACE**

(75) Inventors: Jyrki Suutari; Tolvo Lallukka, both of Oulu; Arto Rukajärvi, Oulunsalo; Olli Liinamaa, Oulu, all of (FI)

(73) Assignee: Nokia Telecommunications Oy, Espoo (FI)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/336,862

(22) Filed: Jun. 21, 1999

Related U.S. Application Data

(63) Continuation of application No. PCT/FI98/00198, filed on Mar. 5, 1998.

Foreign Application Priority Data

Mar. 18, 1997 (FI) 971142

(51) **Int. Cl.⁷** H04Q 11/04; H04Q 3/00; H04M 7/00

(52) **U.S. Cl.** 370/217; 370/228; 370/522; 379/279

(58) **Field of Search** 370/216, 217, 370/220, 225, 228, 254, 357, 360, 401, 410, 420, 422, 426, 522, 524; 340/825.01, 825.03, 826, 827; 379/93.05, 93.07, 268, 279, 230; 714/2, 3, 4

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,418,776 * 5/1995 Purkey et al. 370/16

5,751,574 *	5/1998	Loebig	364/187
5,781,623 *	7/1998	Khakzar	379/230
5,910,980 *	6/1999	Ogasawara et al.	379/142
6,069,948 *	5/2000	Yrjana	379/230

FOREIGN PATENT DOCUMENTS

0792079 A1 *	8/1997	(EP) .
WO 96/17484	6/1996	(WO) .
WO 97/16936	5/1997	(WO) .
WO 97/35404	9/1997	(WO) .

OTHER PUBLICATIONS

A. Gillespie "Interfacing Access Networks to Exchanges: The ETSI V5 Approach" *IEEE Global Telecommunication Conference*, vol. 3, pp. 1754-1758, Dec. 1992.
K. Khakzar "V5 Interfaces between Digital Local Exchanges and Access Networks" *Frequenz*, vol. 48, No. 1-2, ppl. 44-50, 1994.
International Search Report for PCT/FI98/00198, Apr. 9, 1998.

* cited by examiner

Primary Examiner—Alpus H. Hsu

(74) *Attorney, Agent, or Firm*—Altera Law Group, LLC

ABSTRACT

The present invention relates to a procedure for ensuring the operation of signalling channels in a V5 interface between a local exchange (LE) and an access node (AN). The interface includes at least two links (L), in conjunction with redefinition of the interface composition. Redefinition generally involves making changes in the V5 interface data, such as the location of signalling channels on the links. According to the invention, the operation of protected channels in conjunction with restarting is ensured by starting the protected channels on the channels defined for them in the new composition and on the channels to which they were transferred in conjunction with the protection switch-over.

5 Claims, 1 Drawing Sheet

